Harry S. Truman Reservoir Flood Control Operations

An overview of operations

Water Management Section


Hydrologic Engineering Branch

Kansas City District

October 2010



US Army Corps of Engineers
BUILDING STRONG®



U.S. Army Corps of Engineer Kansas City District



- Total of 18 USACE lakes
- Total 11Bureau of Reclamation lakes



Osage River Basin

~15,000 square miles

Lakes in Kansas:


- Melvern
- Pomona
- Hillsdale

Lakes in Missouri:

- Stockton
- Pomme De Terre
- Harry S. Truman
- Lake of the Ozarks, Bagnell Dam



Water Management



- WM's job is to regulate
 KCD lake releases
- KCD water flows contributes to Mississippi River, impacting
- This requires coordination to follow regulations



Authority

Construction of Harry S. Truman Reservoir:

- Flood Control Act of 1954
- Flood Control Act of 1962

Regulation:

Lake Regulation Manual





Authorized Purposes Harry S. Truman Reservoir

- Flood Control
- Hydroelectric Power Production
- Water Supply
- Recreation
- Fish and Wildlife





Flood Control Operations

Harry S. Truman Dam

Lake Regulation Manual

- ► Flood Control Storage Zones: Phase lines
- ➤ Control Points: Specific location downstream with measured flow
- ➤ Osage System Operation
 - Tandem Balance Limiting releases from Corps lake projects upstream of Truman
 - Bagnell Dam Coordination of releases looking downstream

Harry S. Truman Operations

Pool Elevations as Defined by the Lake Regulation Manual:

Surcharge Operations – pool elevation 739.6 ft or greater

to preserve the structure with out unduly endangering downstream communities

Flood Control Operations – pool elevation 706.0 ft to 739.6 ft

regulation of flood control storage by evacuating water accumulated in the exclusive flood control storage space as rapidly as downstream channel capacities and flow conditions permit


Power Operations, multipurpose - pool elevation 704.0 ft to 706.0 ft


operations governed by various agreements to preserve/balance/consider interests of all stakeholders




Harry S. Truman Reservoir

Significant Reference Elevations





Control Points and Associated Flow Limits



Criteria flows

St. Thomas:


Phase I: 34,000 cfs Phase II: 54,000 cfs Phase III: 80,000 cfs

Hermann:

Rising: 260,000 cfs Falling: 90% of crest



Tandem Balance




Reservoirs located such that a release from one becomes inflow to another are subject to tandem balancing.

Tandem balance limits releases from an upstream project when downstream flood control storage would otherwise be disproportionately filled.

The upstream lake projects
Melvern, Pomona, Hillsdale,
Pomme De Terre, and Stockton are
operated in tandem with Harry S.
Truman Reservoir.

Inflows



Approximately 1,400 square miles of uncontrolled drainage area upstream of Bagnell Dam.

Approximately 8,000 square miles of uncontrolled drainage area upstream of Harry S. Truman Dam.

Inflow forecasts to account for runoff from these uncontrolled areas are essential to scheduling releases and by extension, hydropower.



Daily Coordination

WM communicates daily with the following:

- National WeatherService
- U.S. Geological Survey
- Southwestern PowerAdministration
- Ameren









Daily Data Collection and Exchange

- NWS to USACE
 - ▶ Lake inflow forecast
 - ► River flow forecast
 - ▶ Precipitation records
 - ► Forecasted precipitation
- USACE to NWS
 - ► Lake release changes
 - ► Lake forecasts: web-based reports, publicly accessible
- USGS
 - ► River and lake gages








USACE KCD Daily Reports:

http://www.nwk.usace.army.mil/watermanagement/



	WHO WE ARE District » Wate	-	нізтог	RY	- Straight - Straight -			SEARCH		
	District » Wate	-								
	RAW Text Version Kansas City District Lake Forecast									
		10 Sep 2		Day		Day :		Day :		
	MPP	Elevation	Outflow	Elevation	Outflow	Elevation	Outflow	Elevation	Outflow	
Bavins Pt.			45000		45000		45000		45000	
Canopolis	1463.0	1466.96	148	1466.92	146	1466.88	144	1466.84	142	
Vilson	1516.0	1515.44	13	1515.43	13	1515.42	13	1515.41	13	
larlan Co	1945.7	1944.99	250	1944.96	250	1944.93	250	1944.90	250	
1ilford	1144.4	1144.35	25	1144.39	25	1144.43	25	1144.47	25	
uttle Creek	1075.0	1077.30	3000	1077.00	3000	1076.68	3000	1076.35	3000	
erry	891.5	893.28	25	893.28	25	893.27	25	893.26	25	
Clinton	875.5	875.50	21	875.47	21	875.44	21	875.41	21	
mithville	864.2	864.28	8	864.27	8	864.26	8	864.25	8	
.ongview	891.0	891.21	13	891.20	13	891.18	13	891.16	12	
Blue Springs	802.0	802.51	24	802.49	22	802.47	21	802.45	20	
Melvern	1036.0	1035.62	20	1035.63	20	1035.63	20	1035.62	20	
	974.0	973.44	15	973.44	15	973.44	15	973.44	15	
omona			24	916.58	24	916.57	24	916.55	24	
Pomona Hillsdale	917.0	916.58	24							
tillsdale	917.0 867.0	916.58 866.94	40	867.05	40	867.12	40	867.19	1000	
				867.05 839.10	40 2000	867.12 838.85	2000	867.19 838.47	1000 1200	
Hillsdale Stockton	867.0	866.94	40							
tillsdale Stockton Pomme de Terre	867.0 839.0	866.94 839.37	40 2000	839.10	2000	838.85	2000	838.47	1200	

Kansas City District, Water Management Section Department Line: (816) 389-3545



Southwestern Power Administration



- Schedule power generation for parts of Arkansas, Kansas, Louisiana, Missouri, Oklahoma, and Texas from 24 USACE multipurpose dams
- Memorandum of Understanding (MOU) with KCD
- Coordinates Stockton and Truman releases for power generation

Memorandum of Understanding


USACE and SWPA

- ▶ Information exchange
 - USACE: water available
 - SWPA: power needs
- ▶ Daily lake inflow
- ▶ Downstream flooding: USACE may shut down
- ▶ Truman Firm Power
 - Regardless of downstream conditions
 - 2 units for 2 hours
 - Once per 24 hours, midnight to midnight



Ameren

- Lake of the Ozarks,
 Bagnell Dam
- Memorandum of Agreement (MOA)
- Daily coordination






Memorandum of Agreement

USACE and Ameren

- ► Ameren will curtail release at USACE request due to downstream flooding
- ► Ameren may pass their local inflows during flood events
- ► Ameren and USACE coordinate releases from both projects on a daily basis



Lake of the Ozark's 2010 Guide Curve



Consensus Operating Plan

Agreement among State of Missouri, SWPA, and USACE until pumpback is viable

- Defines rules for power generation operation
 - ► Establishes rate of taking off or bringing on units
 - ▶ Quantifies wait time before changing more units
 - ▶ Defines conditions which require minimum of one unit to run continually
 - ► Addresses weekday peaking operations
 - ► Addresses weekend and holiday operations




Summary of Harry S. Truman Reservoir Operations

- USACE operates Harry S.
 Truman Reservoir to balance all authorized purposes
- •Numerous Federal, State, and local stakeholders interests are considered when regulating reservoir releases



Thank you for your interest



in Harry S. Truman Reservoir.